

08-16, day 24.08. 2021

EN– Key depository manual KB.G1

Follow these steps to open the depository.

1. For uncover the dial, pull down the safety cover.
2. Set the factory code number by turning the dial (the factory code is 0-0-0-0).
3. Open the door, and put in or take out the keys.
4. Close the door and turn the dial, for not to be seen the opening code.
5. Slide safety cover onto depository.


Setting your own number code:

1. Open the key depository (see the instructions above) so that the inner door is opposite to you (the RESET button should be on the left side). Press the RESET lever to the right and up on the back side of the door (see on the picture n. 1).
2. Set your own code by turning the dial. Make sure, that numbers are straight in line (see on the picture n. 2).
3. Press the RESET lever down and to the left – back to original position. Make sure, that RESET lever is completely in original position.
4. Press the ratchet and make sure, that the movement down is smooth (see on the picture n.1). Now you set your own number code.
5. Close the door, lock the depository by using your own code and turn the dial for not to be seen your own code.
6. Slide safety cover onto depository.

Important:

1. The safety cover protecting against weather conditions should be kept closed, ensuring better endurance.
2. We do not recommend to use the code number as a “1-1-1-1” because it is easy to crack.
3. We recommend you to turn the dial once a week, for problem-free function of the depository dial.

Pic. 1



Pic. 2



Mounting
holes position

